LPHA FLOW AMF-3CV

P3 DISPOSABLE RESPIRATOR



The Alpha Flow SERIES has been designed to improve comfort and performance whilst maintaining a secure fit. Colour coding the range makes identification simple and easy when varying levels of protection may be required.

FEATURES

- Large surface area ensures very low breathing resistance
- New large exhalation valve which reduces heat build-up and improves wearer comfort
- Colour coded alphamesh shell for ease of identification
- Adjustable headstrap allows for a secure and comfortable fit
- Metal-free suitable for food industry applications
- Preformed nosebridge eliminates the need for regular adjustment
- Compatible with a wide range of safety eyewear
- Soft flexible mesh maintains it's shape and will not collapse during use
- Conforms to EN 149: 2001 + A1: 2009 FFP3 NR



PREFORMED NOSEBRIDGE

Ensures excellent fit without the need to keep adjusting while wearing



NEW MESH DESIGN Lightweight, flexible and will not collapse during use







ORDERING INFORMATION

Part Number: AMF-3CV

Packaging: 10 singles per box

10 boxes per case

Certification: EN149: 2001 + A1: 2009

FFP3 NR

SUITABLE APPLICATIONS

Recommended applications include:

- Craft Work
- Cutting and Casting of Metals
- Disposal of Toxic Waste
- Hospital
- Iron and Steel Industry
- Laboratory and Disease Control
- Manufacture of Batteries
- Mining
- Pharmaceutical industry
- Textile industry
- Underground Civil Engineering
- Woodworking
- Welding work



LPHA FLOW AMF-3CV



P3 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

COMPONENT	MATERIAL			
Mesh Shell:	Polypropylene			
Filter Outer Layer:	Polypropylene			
Filter Inner Layer:	Polypropylene			
Filter Internal Media:	Melt-Blown [Polypropylene]			
Headstrap:	Woven Elastic [Latex-Free] Rubber			
Headstrap Adjuster:	Polypropylene			
Exhalation Valve - Valve Housing:	Polypropylene & ABS			
Valve Membrane:	Synthetic Rubber			
CV Pre-filter:	Activated Carbon Loaded Polypropylene			
Inner Face Seal:	PVC Foam			

DIMENSIONS

ITEM	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	
Respirator	155	70	125	
Nosebridge	25	50	35	
Headband	700	9	0.4	
Headband clip	57	12	9	
Valve	43	43	10	

CERTIFICATION

EC-Type Examination Certification according to European Council Directive 89/686/EEC and subsequent amendments, certified by BSI, Kitemark House, Maylands Ave, Hemel Hempstead HP2 4SQ.

Notified Body: INSPEC International Ltd., 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, UK. [N.B. No. 0194]

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

E١	Approval N 149: 2001 - A1:2009	Mesh Colour	Product Codes	APF (Assigned Protection Factor) (x WEL)	Non-Toxic Dusts	Fine / Toxic Dusts / Mists / Fumes	VeryFine / Toxic Dusts / Mists / Fumes	Odours/ Organic Vapours (Below WEL)	Metal Fumes	Oil/Water Based Particulates
	FFP1 NR	White	AMF-1	4						
	FFP2 NR	Blue	AMF-2	10	0				0	
	FFP2 NR	Blue	AMF-2V	10	0				0	
F	FFP3 R D ◢	Orange	AMF-3V	20	0				0	
	FFP3 NR 🚄	Grey	AMF-3CV	20	0					

