


TECHNICAL DATA SHEET



LEMAITRE SÉCURITÉ S.A.S.
 B.P. 90024
 17, route de Bitschhoffen
 67350 La Walck - France
 Tel: +33.388.72.28.80
 Fax: +33.388.07.05.37
www.lemaitre-securite.com



Style
**RIGGER WOOL
 S3 CI**

Sizes
**EU : 38 to 48
 UK/AU/NZ : 5 to 13**

Description
**FUR-LINED
 HIGH LEG BOOT
 WITH FULL GRAIN
 LEATHER**

UPPER specifications

Leather Water-resistant full grain leather
 2.2-2.4mm thick
 Vamp lining Synthetic fibre in polyester and
 polypropylene
 Quarter lining Synthetic fibre in polyester and
 polypropylene
 Heel stiffener Synderme

FITTING specifications

Last Wide fitting, according to Natur'Form
 concept
 Toe cap Wide ABG toe cap, 200 joules
 according to norm EN 345-1

SOLE specifications

Construction California.
 Insole Antistatic Texon 2.0mm thick
 Arch support Polyethylene anatomic insock with
 integrated arch support
 Sole material Dual-density polyurethane
 • midsole density: 0,50
 • outsole density: 1,00
 Sole resistance Oil and acid resistant
 Heat resistance up to 180°C

Anti-perforation midsole in stainless steel

Advantages

- Water-resistant leather
- Synthetic fur lining
- Height of Upper: 295 mm for size 42/8
- Cold insulation of sole complex (CI)
- Excellent comfort even in extreme flexing conditions
- **Sole with Parabolic® profile**: the concave structure of allows a progressive deformation of the sole in order to optimize the grip to industrial floors
- **Exceptional slip resistance**: the footprint adapts itself to the nature of the ground due to the profile of the sole
- **Suppleness and comfort**: sole design and cramps associate suppleness and adherence for a better comfort
- **Spring effect**: gives a more dynamic walk

Protection

- According to norms EN 344-1 and EN 345-1
- Toe cap: 200 joules
- Anti-perforation midsole: 1250 N
- **S3**: basic requirements + closed back + antistatic + energy absorption at heel + oil resistance of outsole + cleated outsole + water-resistant upper + penetration resistance

Weight

820g / 28.9oz per foot (for size 42/8, ± 5%)

European standard: CE certificate N°: **0075/007/161/08/99/0078 – EXT 18/08/99**. This product has been subjected to CE type approval tests made by a notified body according to norms **EN 344-1 and EN 345-1**.



LEMAITRE SÉCURITÉ
 is certified
ISO 9001 : 2000



Markings (on tongue): Size, manufacturer's identification, identification of model, month and year of manufacture, reference of applicable standard, type of protection, CE mark.