

TECHNICAL DATA SHEET



17, route de Bitschhoffen
F 67350 LA WALCK
Tel : 03.88.72.28.80
Fax : 03.88.07.05.37

www.lemaitre-securite.com

M.A.Healy & Sons Ltd.
Wexford Road, Arklow
Ph: 0402 31402
Strand Street, Passage West
021 4841370
info@mahealy.ie



Style: **SIROCCO S3 CI**
Size: UK 5-13 EU 38-48

Description : High shoe in black water repellent full-grain leather
Toe cap in polycarbonate resistant to 200 joules
Anti-perforation insert in para-amide

er specifications:

Leather: Water repellent black full-grain leather, 2,2 mm thick
Tongue: Water repellent full-grain leather
Collar: in leather
Stiffener: Synderme
Quarter lining: Cambrelle® and 100% polyester.
Fastening: Plastic bodkins
Laces: Polyamide, resistance to abrasion (> 15000 frictions under 250 g in accordance to the norm DIN4843)

Fitting specifications:

Shape: Natur'Form concept
Toe cap : 200 joules according to norm EN ISO 20345

Sole specifications:

Construction: California
Insole: Para-amide
Arch support: Polyethylene anatomic insole
Sole: Dual density polyurethane sole resistant to 90°C

- midsole density : 0,50
- outsole density : 1,00

Anti-perforation insert in para-aramide

Weight: 1320 g

Avantages:

- Water repellent full-grain leather with a very good resistance to external aggressions.
- Sewing reinforcement on the uppers
- Isotherm sole in dual-density polyurethane,
- Antistatic sole resistant to acids and hydrocarbons
- Excellent comfort even in extreme conditions (flexion)
- *Sole with Parabolic profile®*: the concave structure allows a progressive deformation of the sole in order to optimize the grip to industrial floors
- *Double density window®=better absorption of the heel*
- *Exceptional slip resistance*: the footprint adapts itself to the nature of the ground due to the profile of the sole
Adhesion coefficient: 0,21
- *Spring effect*: gives a more dynamic walk.
- Additional toe protection : additional integrated protection reduce the wear effect when it is used for a flexion of the foot
- Delimited heel: for a better safety. An additional precaution in different situations like climbing a ladder for instance

Protection:

- According to norms EN ISO 20344 and EN ISO 20345
- *Polycarbonate toe cap* - 200 joules resistance, twice more lighter than steel
- *Anti-perforation insert in para-aramide*
- *Non metallic protections*: no more problems with the electromagnetic metals detectors in the airports or in securities controlled places and insensible to thermal shocks.

European standards: CE certificate n°: in process

This product is being subjected to CE type approval tests made by a certified body according to norms EN ISO 20344 et EN ISO 20345.

Markings (on tongue): Size, manufacturer's identification, identification of model, month and year of manufacture, reference of applicable standard, identification of the model, type of protection, CE mark



9 FEVRIER 2006
DON/LS.03.0916.B