



**SANTO S3 CI SRC**  
**LOW SHOE IN WATER**  
**REPELLENT PULL UP AND**  
**OILED LEATHER**  
**WITH LIMITED STITCHINGS**

## PROTECTIONS FOR THIS MODEL



Sizes available : 38 (5) to 48 (13)  
 Weight of one pair in size 42 (8) : 1370 gr.  
 Norm EN ISO 20345 : 2007  
 AET : 0161/18485/12

## Upper features

- Upper : water repellent pull up and oiled leather - 2,0 to 2,2 mm thickness
- Tongue : full grain leather
- Quarter lining : tridimensional textile
- Collar: synthetic
- Vamp lining : synthetic
- Counter : synderme
- Closing : metallic fastenings
- Laces : polyamide
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking.

## Protections (sole and cap)

- Toe cap : polycarbonate (200 joules)
- Anti-perforation insert : in stainless steel (1100 N)






## Fitting features

- Natur'form (large)
- Lasting : California
- Lasting insole : anti perforation textile
- Footbed : foam and textile

## Sole features

- Name : HELIUM
- Material : dual density polyurethane
- Comfort sole density : 0,5
- Color comfort sole : black
- Undermine sole density : 1
- Color undermine sole : grey
- Slip resistance SRA (flat) : 0,53
- Slip resistance SRA (heel) : 0,51
- Slip resistance SRB (flat) : 0,24
- Slip resistance SRB (heel) : 0,20

## Basics and additional requirements of the norm EN ISO 20345 : 2007

-  Steel toe cap
-  Polycarbonate toe cap
-  Aluminium toe cap (200 joules)
-  Steel midsole
-  Non metallic midsole
- A** A Electric resistance – Antistatic shoes.
- CI** CI Insulating sole against cold.
- E** E Heel energy absorption.
- Fo** FO Hydrocarbons resistance of the undermine sole.
- Hi** HI Insulating sole against heat.
- Hro** HRO Heat resistance of the sole.
- M** M Metatarsal protection.
- P** P Perforation resistance.
- Wru** WRU Water repellent upper.



Regarding the norm EN ISO 20345 : 2007, the minimum results for slip resistance to get the SRC certificate are :

SRA (flat) = 0,32  
 SRA (heel) = 0,28  
 SRB (flat) = 0,16  
 SRB (heel) = 0,12

## Advantages = End users benefits

- **2,2mm thickness leather** for the upper for better resistance and durability
- **Composite toe cap** made of injected polycarbonate, ergonomic, light (half the weight of steel), elastic and thermic insulation (not sensitive to variation and heat transfer between -10°C to 40°C.
- **Tridimensional textile lining**, soft and breathable for better comfort
- **Closed back**
- SOLE :**
- **Parabolic® profile**
  - **Exceptional slip resistance** : footprint adapts itself to the nature of the ground due to the profile of the sole
  - **Spring effect** : gives a more dynamic walk
  - **Walking assistance** : the concave structure of allows a progressive deformation of the sole in order to optimize grip and facilitate walking
- **Double density PU** : excellent comfort even in extreme flexing conditions
- **Cleated outsole** and auto cleaning sole thanks to the design of the studs.
- **Defined heel**: sure-footed safety! an additional precaution especially on ladders and **double density window** : improves heel energy absorption
- **Cold insulation** of sole complex (CI)
- **Antistatic**